



RED LION

- Quality Products
- 1 Year Over-the-Counter Warranty
- Pump Hotline 1-800-667-1457



www.redlionproducts.com
Winnipeg, Canada
Minneapolis, MN.

Applications:

Ideal for seepage water or puddles on smooth surfaces.

Performance Table

Height (ft)	5	10	15	17	19
U.S. GPM	20	14	7	4	0

Features:

- 1/6 HP, 115 volt thermal overload protected continuous duty "oil free" motor.
- Corrosion resistant aluminum casing.
- Lightweight portability.
- Bottom suction with built in suction strainer.
- Removable filter screen for easy cleaning.
- 3/4" NPT discharge with garden hose adapter.
- Pumps to 1/4" depth.



Applications:

Ideal pump for removing cellar/ sump seepage water. For use in 12" diameter or larger sumps.

Performance Table

Height (ft)	5	10	15	20	21
U.S. GPM	24	19	12	3	0

Features:

- 1/4 HP, 115 volt thermal overload protected, continuous duty "oil free" motor.
- Corrosion resistant aluminum casing for superior heat dissipation.
- Automatic mercury free mechanical float switch.
- Removable filter screen for easy cleaning.
- 1 1/4" NPT discharge.



RL-300C Column Sump Pump

Applications:

An economical pump for removing cellar/sump seepage water. For use in 12" diameter or larger sumps.

Performance Table

Height (ft)	5	10	15	18
U.S. GPM	42	30	8	0

Features:

- 0.3 HP, 115 volt motor.
- Corrosion resistant construction.
- Automatic, float activated switch.
- Adjustable start/stop levels.
- 9 Foot power cord.
- 1 1/4" NPT Discharge.
- Flow rates to 42 U.S. GPM.
- Stable 9 1/2" dia. base.



RL-330S Submersible Sump Pump

Applications:

Ideal pump for removing cellar/ sump seepage water. For use in 12" diameter or larger sumps.

Performance Table

Height (ft)	5	10	15	20	23
U.S. GPM	33	23	16	5	0

Features:

- 1/3 HP, 115 volt thermal overload protected, continuous duty "oil free" motor.
- Stainless steel internal motor housing for maximum reliability.
- Fully corrosion resistant, reinforced thermoplastic construction.
- Automatic mercury free mechanical float switch.
- Removable filter screen for easy cleaning.
- 1 1/4" NPT discharge.



RL30E/SA - RL30E/SV Submersible Sump-Effluent Pumps

Applications:

Ideal for both residential cellar sump drainage, as well as liquid effluent pumping applications with up to 1/2" diameter solids.



Performance Table

Height (ft)	5	10	15	17.5
U.S. GPM	44	33	13	0

Features:

- Standard Automatic or vertical (as shown) float switches available with 10 foot power cord.
- 1/3 HP, 115 V thermal overload protected, continuous duty "oil free" motor, in durable cast iron housing.
- Corrosion resistant polypropylene pump casing.
- 1 1/2" Discharge with 1 1/4" reducer bushing.
- Flow rates to 44 U.S. gallons per minute.

RL52SA Submersible Sewage Pump

Applications:

Ideal for residential raw sewage applications, as well as light commercial applications with up to 2" diameter solids.



Performance Table

Height (ft)	5	10	15	20	23
U.S. GPM	135	90	47	14	0

Features:

- 1/2 HP 115 volt thermal overload protected, continuous duty motor.
- Rugged cast iron construction.
- Heavy duty cast iron pump base and impeller.
- 2" NPT discharge.
- Automatic float switch with 20 foot power cord.
- Flow rates to 135 U.S. gallons per minute.

RL52SVX Submersible Sewage Pump

Applications:

Ideal for residential raw sewage applications, as well as light commercial applications with up to 2" diameter solids.



Performance Table

Height (ft)	5	10	15	18
U.S. GPM	112	80	40	0

Features:

- 1/2 HP, 115 volt thermal overload protected, continuous duty "oil free" motor.
- Rugged cast iron construction.
- "Non clogging" vortex impeller design.
- 2" NPT discharge.
- Automatic float switch with 20 foot power cord.
- Flow rates to 112 U.S. gallons per minute.

RL31EA Submersible Effluent Pump

Applications:

Ideal for liquid effluent pumping applications, as well as light commercial applications with up to 11/16" diameter solids.



Performance Table

Height (ft)	5	10	15	20	25	28
U.S. GPM	105	90	70	45	15	0

Features:

- 1/3 HP 115 volt thermal overload protected, continuous duty motor.
- Rugged cast iron construction.
- Heavy duty cast iron pump base and impeller.
- 2" NPT discharge.
- Automatic float switch with 20 foot power cord.
- Flow rates to 105 U.S. gallons per minute.

RL-S Series Self Priming Effluent Pump

Applications:

Ideal for pumping liquid effluent from septic tanks, as well as pumping out flooded basements, irrigation and general dewatering.



Features:

- Rugged cast iron pump casing with check valve.
- Cast iron impeller.
- Self priming to 25 feet.
- 1 1/4" NPT suction and discharge.

Pump Model No.	HP	Pump Capacity in U.S. GPM							Max. Ht. (ft)
		Pumping Height in Feet							
		20	25	30	35	40	45	50	
RL-S33	1/3	36	30	23	16	9	2	0	46
RL-S50	1/2	45	39	31	24	16	8	0	49
RL-S75	3/4	58	53	44	36	29	18	10	56

RL52SVX-35 Submersible Sewage Pump & Receiver Tank System

Applications:

Ideal for residential raw sewage applications, as well as light commercial applications with up to 2" diameter solids.



Performance Table

Height (ft)	5	10	15	18
U.S. GPM	112	80	40	0

Features:

- Fully assembled sewage system, ready to install.
- RL52SVX Submersible Sewage Pump.
- Receiver tank - 35 U.S. gallon tank (18" diameter x 30" high) made of high density thick walled polyethylene.
- 2" NPT ABS Plastic check valve with 2" pipe.