SEWAGE BASIN SYSTEMS

APPLICATIONS

Ideal for the collection and removal of sewage, effluent, drainage or seepage water from low lying areas.

FEATURES & BENEFITS

- 18" x 30" polyethylene basin
- 2" full-flow sewage check valve
- Cover assembly and hardware
- Includes 1/2 hp sewage pump
- Discharge pipe - pump to basin cover
- Heavy-duty cast iron pump base and impeller
- Automatic piggyback float switch

Model	Item Number	UPC	HP	Amps	Volts	Discharge	Cord Length	Gallons Per Hour at Height					Shut-Off	On/Off Levels	Assembly Required
								0'	5'	10'	15'	20'			
RL-WCS50TA	14942749	0 10121 14172 8	1/2	9	115	2" FNPT	10'	5600	4920	3720	1680	480	22'	On: 17.5" Off: 7.5"	Assembly Required
RL52WSPX	620061	0 10121 13856 8	1/2	11.4	115	2" NPT	20'	9000	7200	6000	4500	960	22'	On: 16"–18" Off: 9"–11"	Fully Assembled

Carton Specifications

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Qty. per Layer	Layers per Pallet
RL-WCS50TA	18"	18"	36"	55	6.75	4	2	2
RL52WSPX	18"	18"	36"	61	6.75	4	2	2